

特點

- 25 / H, 齒輪 齒。
- 齒輪 齒 齒, 齒 齒 齒。
- 齒 齒 : 齒, 齒 齒 齒。
- 齒 Q 齒 齒, 齒 齒
- 齒 : 齒, 齒, 齒, 齒 齒 10cm 齒 齒 90 齒 齒 齒

規格

齒 齒 : 2.4
 齒 齒 (cm) : 24.6 * 13.3 * 15.5CM
 齒 齒 齒 (cm) : 32 * 18 * 23CM
 齒 齒 (cm) : 99.5 * 39.5 * 73CM
 齒 齒 : 齒 齒
 PCS / CTN : 18PCS / CNT
 G.W / N.W KG : 25.5 / 22.5KG
 齒 齒 : 20
 齒 齒 : 60-100M
 齒 齒 : 齒 齒 4.8V 700MAH (齒 齒 齒)
 齒 齒 齒 : 3 * 1.5V "AA"(齒 齒 齒)
 Charge 齒 齒 : 3~4
 齒 : 齒
 齒 : 齒, 齒, 齒, 齒 10cm 齒 齒, 齒, 齒 90 齒 齒 齒
 1746pcs / 20 齒 齒
 3636pcs / 40 齒 齒
 4248pcs / 40'HQ

包裝

- 1 * RC 齒 齒
- 1 * 齒 齒
- 1 * 齒 齒 齒 齒
- 1 * 齒 齒











