

□□□□

- 70KM / H, □□ □□ □□.
- □□ : □□ / □□□, □□□ / □□□□

□□□

□□□ : 2.4  
 □□ □□ (cm) : 24.5 \* 17.5 \* 9.4CM  
 □□ □□ □□ (cm) : 46.2 \* 25 \* 24.5CM  
 □□ □□ (cm) : 52.5 \* 49.5 \* 76.5CM  
 □□ □□ : □□ □□  
 PCS / CTN : 6PCS / CNT  
 G.W / N.W KG : 13.49 / 11.28KG  
 □□ □□ : □□  
 □□ □□ : 100M  
 □□□□ □□□□ : 7.4V / 1500MAHLi □□ □□□ □□□ □ □□  
 □□□□ □ □□□ : 4 \* 1.5V "AA"(□□□□ □□)  
 Chargin □□ : 180mins  
 □□ : □□  
 □□ : □□ / □□□, □□□ / □□

□□ : 70KM / H

840pcs / 20 □□ □□□□

1746pcs / 40□□ □□

2046pcs / 40'HQ

□□□□ □□

- 1 X □
- 1 X □□ □□
- 1 X □□□
- 1 X □□□
- 1 X □□□□ □□
- 1 X □□
- 1 X □□□





## Overview



REMOTE CONTROL



TRANSVERTER



WITHDRAWAL TOOL



SPECIFICATION



CHARGER



POWERFUL MOKTOR

MAXIMUM SPEED 70KM/H





## INDEPENDENT SUSPENSION

EFFECTIVELY REDUCE THE VIBRATION  
OF CAR BODY FRICTION



## RUBBER WHEELS

INCREASE THE THICKENING OF THE RUBBER WHEEL  
MORE SLIPPERY WEAR-RESISTING





Specification

